

**Project:** 



Scan for more info! Owners manual Quick install Quick sizing Install layout Parts list

# CR-UCM2-SW-2 Remote Chiller Two Coil Unit



0

# Chilled water on tap

Designed for remote or backhouse mounting applications: Up to 45' Has double water loop, with two water outlets. Can be used for a CBR-V2 with two still water options, or two separate CBR-V1 towers Multi-tower station configuration possible Increased chilling capacity


### **Specifications**

- 68 liters/18 gal per hour @<40°
- Self-contained refrigeration system
- Compressor: 1/3 H.P.
- Refrigerant: R134a CFC-free
- BTU: 2,400 per hour Ave
- Operating temperature range: 40°-100°
- Electrical: 120v 7.7 Amps


- Water Bath: 6 Gallons
- Ice Bank: 25 lbs
- Weight: 135 lbs
- 20"W x 20"D x 20"H

Crysalli Beverage Systems a division of WPD 1739 Sabre Street, Hayward, CA 94545 www.crysalli.com

510.732.0100



- 3/8" OD Chilled water outlet
- 3/8" OD Water inlet fitting
- 7' Water bath overflow drain hose
- 9' Electrical cord
- Remotely locate system up to 45' away from tower



- Allow for 8" of clearance above the unit for service and access to water bath
- 3/8" OD Re-Circ fittings

Four line insulated trunk

line 3/8" Two Product, two

recirculating 5' is included

in Remote Chiller Install Kit

Provide a well ventilated space with 6" clearance around the sides of the unit

# Accessories

- □ CR-24FCP with Prefilter
- □ CR-24FC without Prefilter Twin filter system with compact fibredyne filters, 19"H x 17"W 5 gpm, 30,000 gal, TOC & 1/2 micron filtration



- □ CBR-V1C
- □ CBR-V1WHT Single valve, single product One SSQ adjustable flow faucet



water chillers, CR-UCW, CR-UCM2-SW2 & CP2000-SW-BH, Includes: 5' of CR-4L38 trunkline, various fittings and oetiker clamps, adapters, and extra tubing Still Water Units Only



□ CBR-V2C □ CBR-V2WHT

KCL IM | CAD | MOBILE

Two valve, two product Two SSQ adjustable flow faucets



□ RDP-1SSO-1CL

□ CR-4L38

□ RDP-1SSQ-2CL Flush mount, stainless drain pan and tower mount. For use with single or two product towers



#### CR-ABUCM Air Baffle Accessory



CR-WMB-2 Wall Mount **Bracket** 



DP-CT Stainless countertop mount drain pan, 1/2" drain pipe





Crysalli Beverage Systems a division of WPD 1739 Sabre Street, Hayward, CA 94545

NS

Intertek

www.crysalli.com

510.732.0100 CR07022020